


VPKCF8
VPKCF12
VPKCF15
VPKCF20



SYMBOL



FEATURES 特點

Model	Operating Pressure (Kgf/cm ²)		Rated Speed (rpm)		Net Weight
			MAX	MIN	
VPKCF8	A1: 5-18 A3:30-55	A2:15-35 A4:50-70	1800	800	4.8Kg
VPKCF12	A1: 5-18 A3:30-55	A2:15-35 A4:50-70	1800	800	4.8Kg
VPKCF15	A1: 5-18 A3:30-55	A2:15-35 A4:50-70	1800	800	5.2Kg
VPKCF20	A1: 5-18 A3:30-55	A2:15-35 A4:50-70	1800	800	5.2Kg

ORDERING CODE 訂購指引

VPKC-F*A*-01-A

① ②③ ④ ⑤ ⑥

- ①—— Series Number
- ②—— Flange Type
- ③—— Output Flow at 1800rpm
8,12,15,20 (ℓ/min)
- ④—— Pressure Adjusting Range
1:5-18 2:15-35 (Kgf/cm²)
3:30-55 4:50-70
- ⑤—— Shaft Type
01:No.01 Shaft
02:No.02 Shaft
- ⑥—— Type of Suction Port & Discharge Port
A or No Marking: PT
B: NPT
C: SAE
D: BSP