

Datasheet 2SIE 225M4 B3

General data

Article no.:	1422M004035IE2B
3-Phase motor type:	2SIE 225M4 B3
Output:	45 kW
Manufacturer:	Cantoni Motor
Frame size:	225
Number of poles:	4
Efficiency class:	IE2 High Efficiency
Flange/feet:	Feet
Mounting:	B3 (IM 1001) or derivatives
Isolation class:	F (155°C) temperature rise-class B (80K)
Duty type:	S1 (continuous)
Ambient temperature:	-20 to +40°C
Altitude:	≤ 1000 m.a.s.l.
Service factor:	1
Cooling method:	IC411 (TEFC)
Protection:	IP55
Tropicalisation:	No
Motor weight:	395 kg

Electrical data (calculated values)

Rated Voltage (U_N):	400	690	V
Rated frequency (F_N):	50	50	Hz
Connection:	Δ	Y	
Rated output:	45	45	kW
Rated speed:	1484	1484	rpm
Efficiency:	93,6	93,6	%
Power factor:	0,84	0,84	
Rated current:	83,0	47,9	A
Starting current:	630,8	364,2	A
Factor starting current:	7,6	7,6	
Nominal torque:	290,00	290,00	Nm
Starting torque:	609,0	609,0	Nm
Factor starting torque:	2,1	2,1	
Breakdown torque:	812,0	812,0	Nm
Factor breakdown torque:	2,8	2,8	

Load characteristics

Load:	0	25	50	75	100	125	%
Efficiency at 50Hz:			93,0	93,8	93,6		%
Efficiency at 60Hz:							%

Datasheet 2SIE 225M4 B3

Mechanical data


Moment of inertia:	0,55 kgm ²	Painting:	RAL 5010 (Gentian Blue)
Sound pressure level:	According IEC 60034-9	Frame material:	Cast Iron
Bearing DE:	6313 C3	Shields material:	Cast Iron
Bearing NDE:	6313 C3	Feet material:	Cast iron - integrated
Bearing system:	Regreasable	Terminal box position:	Top
Bearing fixation:		Cable glands size:	M50 (2x), M16 (1x)
Balancing vibration class:	A (half-key)	Cable glands direction:	To right
Direction of rotation:	CW or CCW		

Shaft

Shaft dimensions:	Ø60 x 140 mm
Key dimensions:	125 x 18 x 11 mm
Thread of center hole:	M20


Horizontal operation:

$F_R (X=0)$	4,1 kN
$F_R (X=\max)$	3,3 kN



Vertical operation:

F_p	3,2 kN
F_{a1}	2,3 kN
F_{a2}	4,2 kN



Standards

Rating and performance:	IEC 60034-1
Methods for determining losses and efficiency:	IEC 60034-2-1
Classification of degrees of protection:	IEC 60034-5
Methods of cooling:	IEC 60034-6
Symbols of construction and mounting arrangements:	IEC 60034-7
Terminal markings and direction of rotation:	IEC 60034-8
Noise limits:	IEC 60034-9
Dimensions and output of electric machines:	IEC 60072-1
Vibration limits:	IEC 60034-14

Special remarks

Inclusive PTC 140°C

Datasheet 2SIE 225M4 B3
